



BayLight® Prismatic Skylights

There's Nothing Greener than Off™

Reasons You Should Select BayLight® For Your Next Metal Building Skylight System

1. A third party test revealed that the BayLight® has the highest lighting performance of any domed skylight system in the market. Ideally suited for the vast array of daylighting applications which enhances a wide variety of indoor activities.
2. Double and triple glazed skylights come standard with an insulated, thermally-broken frame. Reduces any chance of condensation forming on the interior of the skylight frame.
3. All outer dome material is virgin grade, 100% impact modified clear polycarbonate, giving BayLight® domes seven times the impact strength of general purpose polycarbonate domes.
4. BayLight®, with higher visible light transmittance and optimal light distribution, produces daylighting which reduces up to 75% of daytime electric lighting.
5. BayLight® reduces energy consumption resulting in lower utility bills and a cleaner environment while providing higher quality natural lighting.



Double Glazed BayLight®

Our double glazed Tri-Arch dome formation consists of a monolithic polycarbonate outer dome and a prismatic polycarbonate inner dome.

The shape allows for thicker glazing, resulting in a stronger skylight.

The frame is 33% thicker and 26% longer and deeper providing a better fit on your curb.

STANDARD SIZES

Model Size	Rough Opening Dimensions	Outside Curb Dimensions	Inside Skylight Frame
4848	48" x 48"	51"x51"	52 ½" x 52 ½"
4896	48" x 96"	51"x99"	52 ½" x 100 ½"
6072	60" x 72"	63" x75"	64 ½" x 76 ½"



Member of the Bay Family of Companies

For more information, contact your
Bay Insulation District Sales Manager
or call (540) 986-2572.



www.BayInsulation.com