

Bay Insulation



Product Description

| Product | Green Product | Primary Class of Work | Application | Class 1 Type/Rating | Height Restriction | Listing Country | Certification Type |
|----------------|---------------|-----------------------|--------------------|---|-----------------------|--------------------------|--------------------|
| Bay Insulation | GREEN | 4880 | Walls and Ceilings | Exposed Interior Insulation/Combustible | Maximum 30 ft (9.1 m) | United States of America | FM Approved |

Product Specification

| Product | Core Material | Panel Thickness | | Other |
|----------------|---------------|-----------------|------------------|--------|
| | | in | (mm) | |
| Bay Insulation | Glass Fiber | 3 - 9.5 | (76.20 - 241.30) | Faced* |

* FM Approved Lamtec R-3035, R-3035 HD, R-3035 4x4, R-3035 5x5, WMP-F, WMP-VR, WMP-VR-R Plus, WMP-VR-R Plus HD, WMP-10, WMP-30, WMP-50, WCF-30, WCF-50, Arenashield or Gymguard

Interior Installation Requirements

| | |
|--------------------------------|---|
| Flashing | None |
| Sealant/Gasket/Caulking | None |
| Other | Insulations are installed with facing side to the interior, on metal building walls or ceilings over steel supports prior to the installation of the exterior metal siding or roofing. They are held in place when the metal siding or roofing is secured through the blankets into the studs or girts. |

Details

| | |
|----------------------------|--|
| Category | Walls and Ceilings - Interior Use Only |
| Green Product Types | This product contains no CFC or HCFC |
| Class of Work | 4880 - Interior Building Materials |

Company

Bay Insulation of Pennsylvania
 40 Hilton St, Easton ,
 Pennsylvania 18042
 United States of America
<http://bayindustries.com>



Member of the FM Global Group

| | |
|----------------------------|--|
| Application | Walls and Ceilings |
| Class 1 Type/Rating | Exposed Interior Insulation/Combustible |
| Height Restriction | Maximum 30 ft (9.1 m) |
| Certification Type | FM Approved |
| Listing Country | United States of America |