



Industrial Tapes. Since 1973.

Cold Weather Double Coated Polyester Tape DC-M155A

DESCRIPTION

DC-M155A is a high performance double sided polyester film (PET) tape that forms a permanent bond with a wide variety of surfaces. It is coated on both sides with a cold weather acrylic pressure sensitive adhesive.

APPLICATIONS

- Lap seals on laminated and reflective insulation
- Lap seals on pipe jacketing insulation
- Permanent bond of foams, plastics, metals and composite materials
- Insulation mounting under a broad range of environmental and temperature conditions

TECHNICAL DATA

Thickness	3.6 mils
Carrier	Polyester
Liner	White
Adhesive	Acrylic
Adhesion	40 oz/in
Application Temperature Range	-20°C to 120°C / (-4°F to 248°F)
Color	Transparent

Call for samples or additional information.

1.800.461.8273 / www.echotape.com / info@echotape.com

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.