

DESCRIPTION

FS-G7749 is a reinforced metalized white polypropylene film, metallization, fiberglass, and polyester fabric that is combined with a high performance cold weather solvent acrylic adhesive. Features an easy release silicone treated liner. A superior quick stick at normal operating temperatures and great performance at low temperatures.

APPLICATIONS

- Vapor seal / seaming on Lamtec® Gymguard faced insulation
Lamtec is registered trademarks of Lamtec Corporation.

FEATURES

- High performance adhesive
- Good adhesion to Gymguard facing material
- Excellent vapor barrier & low WVTR

TECHNICAL DATA

| | |
|-------------------------|--------------------------------|
| Total Thickness | 9.0 mils |
| Backing Thickness | 7.5 mils |
| Tensile | 190 lbs/in |
| Adhesive | Acrylic |
| Adhesion | 40.0 oz/in |
| Application temperature | -4°F to 104°F (-20°C to 48°C) |
| Service temperature | -40°F to 176°F (-40°C to 80°C) |
| Elongation | 25.0 % |

Call for samples or additional information.

1.800.461.8273 / www.echotape.com / info@echotape.com

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.