
3520CW

FOIL INSULATION TAPE

VentureTape® 3520CW is a 2 mil (50µm) high strength dead soft aluminum foil coated with Venture CW cold weather acrylic pressure sensitive adhesive. The malleable foil applies easily to both fibrous and sheet metal ducts and conforms to irregular surfaces. VentureTape 3520CW excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.

Product Construction



Features & Benefits

- UL723 Listed (5/10 Flame/Smoke Rating)
 UL file # R10984
- Specifically designed for cold weather conditions
- Cold weather acrylic adhesive performs well over a wide temperature range
- Hand tearable allows for easy installation
- In stock product available for immediate delivery

		Typical Value	Test
Test	Typical Value	(Metric)	Method
Product Thickness ^Ω	3.5 mils	0.09 mm	PSTC-133
Peel Adhesion △	50 oz/in	13.9 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	21 lb/in	94.9 N/25 mm	PSTC-131
Elongation	4 %	4 %	PSTC-131
Service Temperature	-40 to 250 °F	-40 to 121 °C	
0	A 00 min to 1 min		

 $^{\Omega}$ - excluding liner $^{\Delta}$ - 20 minute dwell

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

Standard roll widths: 2", 2½", 3", 4"

Standard length: 50Y

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076 From United Kingdom 0-800-962-957 From Australia 1-800-122-797 www.venturetape.com



USA

Venture Tape Corp. 30 Commerce Road Rockland, MA 02370 781-331-5900 FAX 781-871-0065

Europe - Venture Tape

Venture Tape Europe Corp. 1 Sopwith Way Drayton Fields Industrial Estate Daventry, Northhampton NN11 8PB (0) 1327 876555 FAX (0) 1327 876444

Australasia

Venture Tape Australasia, Pty., Ltd. 11B Production Drive Campbellfield 3061 Victoria Australia (03) 9357 6025 FAX (03) 9357 6045