



METAL & POST FRAME BUILDING INSULATION

2500 SERIES

rFOIL® Benefits:

- Blocks 96% of Radiant Heat Transfer
- Prevents Interior Condensation
- Class 1 / Class A Fire-Rated (ASTM E84)
- Puncture and Tear-Resistant
- Unaffected by Humidity
- Will not Promote Mold and Mildew
- Safe, Non-Toxic, and Non-Carcinogenic
- Easy to Handle and Install
- Various Tab Options
- UV-Resistant

rFOIL® Applications:

- Pre-Engineered Steel Buildings
- Post Frame / Pole Barns
- Agricultural Buildings
- Residential Metal Roofs
- Mini Storage
- Livestock Confinement



rFOIL® reflective Insulation is a layer of polyethylene bubbles bonded to and sandwiched between a radiant barrier metalized film surface and a white polyethylene sheet.

rFOIL® is specially designed to reduce radiant heat gain/loss in all residential and commercial applications. rFOIL® also helps control condensation by providing an airtight thermal break while reducing the amount of heat transfer.

Adding rFOIL® Reflective Bubble Insulation to your construction project improves the insulation value of the building envelope and significantly increases its energy efficiency.



METAL & POST FRAME BUILDING INSULATION

(2500 Series)

Reflective Metalized Surface Facing

- Reduces radiant heat gain and loss
- Blocks 96% of radiant heat transfer
- Saves energy use
- Lowers heating / cooling costs
- Improves interior comfort

Multi-Layer Bubble Core

- Provides continuous thermal break
- Lowers risk of interior surface condensation
- Durable and long-lasting
- Superior puncture, tensile, and tear strength
- Will not absorb water or vapor
- Does not harbor moisture or mold
- Clean, safe, no-itch material

White Interior Facing Option

- Brightens building interior
- Attractive appearance
- Easy to clean
- UV Protected

Practical Tab/Edge Options

- Various options for all metal building applications
- Simplifies installations
- Improves vapor-sealing efforts

Quick Seam (Adhesive Tape on Tab)

- Saves time and labor
- Ensures a continuous vapor and condensation barrier
- Simplifies and speeds installation

PRODUCT SIZES

- Width: 12", 16", 18", 24", 48" and 72"
- Length: 102' and 125'

PRODUCT OPTIONS

- Single or Double Bubble
- Square Edge, Tab 1 Side, Tab 2 Sides, Quick Seam Adhesive Strip

PRODUCT SPECIFICATIONS

PHYSICAL PROPERTIES	TEST	2520 SERIES (Double)	2510 SERIES (Single)
NOMINAL THICKNESS	—	5/16"	3/16"
FIRE RATING	ASTM E84-08 / ASTM E2599-08	CLASS 1 / CLASS A	
	ASTM E84-08	FLAME SPREAD=0	FLAME SPREAD=0
		SMOKE DEVELOP=15	SMOKE DEVELOP=10
UV TESTING	ASTM G155	90+% RETAINED RETENTION after 4000 hours	
FIRE RATING - FULL ROOM BURN	NFPA 286	PASSES	
EMISSION	ASTM C1371-04A	0.04	
REFLECTIVITY	ASTM E903	0.96	
WATER VAPOR PERMEABILITY	ASTM E96	0.12 Perms	0.01 Perms
RESISTANCE TO FUNGI and BACTERIA	ASTM C1149	DOES NOT PROMOTE GROWTH	
PLIABILITY	ASTM C1224-03	NO CRACKING	
BLEEDING and DELAMINATION	ASTM C1224-03	NO BLEEDING or DELAMINATION	
CORROSIVENESS	ASTM D3310-00	PASSES	



Warranty, Specific Applications, and Installation Guides can be found at www.rfoil.com

